

Model: HARLEM ACERO C-2(R10) L 120X120(A)

Codes: 100348442

Water absorption: Bla - Porcelanico (E<=0.1%)





DIMENSIONAL FEATURES UNE-EN ISO 10545-2				
Length and width deviation	Below 0.15%	+/-0.3%*		
Side straightness deviation	Below 0.15%	+/-0.3%*		
Squareness deviation	Below 0.15%	+/-0.3%*		
Surface flatness deviation	Below 0.15%	+/-0.4%*		
*ISO-13006:2018 UNE-EN 14411:2016				

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11			
Crazing resistance	Resists 3 cycles		

^{*}ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995			
Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*	
Stain resistance *ISO-13006:2018 UNE-EN 14411:2016	Class 5. Easy cleaning with water	3 Min.*	

	ANTI-SLIP VALUE EN 16165: 2022 / ASTM C1028
Dynamic coefficient of friction	>0,42
Slip resistance (pendulum-wet)	CL2
Slip resistance (ramp)	R-10

^{*}ISO-13006:2018 UNE-EN 14411:2016

	PACKING
Sales units per box	1.440092 M2/BOX
Sales units per pallet	60.483871 M2/PAL
Sales units per unit	1.440092 M2/PIECE

SCOPE OF USE			
Technical code-1	6 - Use on heavy traffic floors		

System Certification









RECOMMENDED USE LOCATIONS

Single-family dwelling

Indoor Premises - Dry: Room, room, bedroom or other enclosure without direct access to the outdoors.

Collective housing

Indoor Premises - Residential - Dry: Entrance, living room, dining room, professional office with reception of customers

Indoor Premises - Housing - Dry: Bedrooms, personal office, storage room, changing room

Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

Kitchen worktops, bars, restaurants

Public bathroom countertops

System Certification





