DECLARATION OF PERFORMANCE 101-DPR-20210518

1. Unique identification code of the product-type:

Dry pressed ceramic tiles with low water absorption E ≤0,5%

2. Intended uses:

Internal and external walls and floorings.

3. Manufactured:

PORCELANOSA S.A.U. Ctra. N-340 Km. 56,2 12540 Vila-real (Castellón) ESPAÑA

4. System(s) of assessment and verification of constancy of perfomance (AVCP).

System 4

5. Harmonized standard: BS EN14411

6. Notified laboratory:

Not applicable

7. Declared perfomance:

CARACTERÍSTICAS	PRESTACIONES
Reaction to fire:	Clase A1-A1 _n
Release of dangerous substance:	
Cadmium	NPD
Lead	NPD
Breaking strength:	≥1300 N
Slip resistance: (UNE41901: 2017 EX)	NPD
Tactility:	NPD
Adhesion:	
Cementitious adhesive, type C2	≥ 1,0 N/mm²
Thermal Shock Resistance	Pass
Durability for:	
Internal use	Pass
Outdoor uses (frost resistance)	Pass

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration of perfomance is issude under the sole responsability of the manufactures identified in point 3.

Name and function: José Meseguer Basiero (proxy) Signature