
# ARGENTA | TECHNICAL DATA





### **BASIC CHARACTERISTICS:**

Pieces name:	GALLERY CUBE DARK HEX(PRC)14X16/ARG30_S
Size (cm.):	14X16
Colour:	DARK
Series name:	GALLERY
Family:	GLAZED PORCELAIN

### **TECHNICAL CHARACTERISTICS:**

Fabrication process:	Dry pressed ceramic tile	
Absorption group (ISO 13006):	BIa	
Finish:	GL	
Rectified:	No	
Body:	STD Body	
Surface Finish:	Matt	
Work size (mm):	140 x 160 x 8,7	
Aesthetic classification and shade variations:	V.1	
Facial dimension range and surface quality:	Complies with the standard	UNE EN ISO 10545-2

#### PHYSICAL CHARACTERISTICS:

Water absorption:	E ≤ 0.5	UNE EN ISO 10545-3
Braking strength (S):	> 1300 N	UNE EN ISO 10545-4
Flexural tensile strength (N/mm2):	≥35 N/mm2	

#### **IMPORTANT NOTES:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the instalation and grouting visit the Argenta website: www.argentaceramica.com/packing-list. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.



## ARGENTA | TECHNICAL DATA



Lineal thermal expansion between 20º to 100ºC	< 9*10-6 / ºC	UNE EN ISO 10545-8
Thermic shock resistance:	Complies with the standard	UNE EN ISO 10545-9
Crazing resistance:	Complies with the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	Complies with the standard	UNE EN ISO 10545-12
CHEMICAL PROPERTIES:		
Resistance to home cleaning products and swimming pool salts:	Clase A	
Resistance to High concentration acids and bases:	Complies with the standard	UNE EN ISO 10545-13
Resistance to Low concentration acids and bases:	Complies with the standard	

#### CE MARKING:



004CPR-PR/11-4-2013

#### **IMPORTANT NOTES:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the instalation and grouting visit the Argenta website: www.argentaceramica.com/packing-list. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

