
## ARGENTA | TECHNICAL DATA FICHA TÉCNICA







BASIC CHARACTERISTICS:		
Pieces name:	JEWELL BLUE (AZJ) 7,5X30 /ARG26_S	
Size (cm.):	7,5X30	
Colour:	BLUE	
Series name:	JEWELL	
Family:	WALL TILE WHITE BODY	

TECHNICAL CHARACTERISTICS:				
Fabrication process:	Single-fired porous white-body tile			
Absorption group (ISO 13006):	BIII			
Finish:	GL			
Rectified:	No			
Body:	White Body			
Surface Finish:	Gloss			
Work size (mm):	75 x 300 x 9,3			
Aesthetic classification and shade variations:	V.2			
Facial dimension range and surface quality:	Complies with the standard	UNE EN ISO 10545-2		

PHYSICAL CHARACTERISTICS:		
Water absorption:	E>10%	UNE EN ISO 10545-3
Braking strength (S):	≥ 600 N	UNE EN ISO 10545-4
Flexural tensile strength (N/mm2):	≥12 N/mm2	

#### **IMPORTANT NOTES:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the instalation and grouting visit  $the Argenta \ website: www.argentaceramica.com. The packing list of this pieces are indicated on the Argenta \ website: www.argentaceramica.com/packing-list. The stated \ argentaceramica.com/packing-list. The st$ weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief. Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

Certifications:





### ARGENTA TECHNICAL DATA



Lineal thermal expansion between 20° to 100°C	< 9*10-6 / ºC	UNE EN ISO 10545-8
Thermic shock resistance:	Complies with the standard	UNE EN ISO 10545-9
Crazing resistance:	Complies with the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	Not apply	UNE EN ISO 10545-12

CHEMICAL PROPERTIES:		
Resistance to home cleaning products and swimming pool salts:	Clase A	
Resistance to High concentration acids and bases:	Complies with the standard	UNE EN ISO 10545-13
Resistance to Low concentration acids and bases:	Complies with the standard	
Resistance to staining:	Complies with the standard	UNE EN ISO 10545-14

# CE MARKING: 003CPR-A/11-4-2013

### **IMPORTANT NOTES:**

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the installation and grouting visit the Argenta website: www.argentaceramica.com. The packing list of this pieces are indicated on the Argenta website: www.argentaceramica.com/packing-list. The stated weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

### Certifications:

