


【Basic Parameters】

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- Size: $\phi 30 \times 300$ mm optional
- IP grade: IP20
- CCT: 2700/3000/3500/4000K optional
- CRI: 90
- SDCM: <3 Step (ANSI)
- Beam angle: 24°/36°
- Light efficiency: 66 lm/W
- Input voltage: DC48V
- Lighting direction: downward
- Dimming method: Non / DALI-2 / Tuya Bluetooth / CASAMBI
- Application: Indoor
- Certification: CE, UKCA, ROHS, Reach
- Warranty: 3 years



【Luminaire Parameters】

Version	Model	Size	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	CRI	Beam Angle	CCT	Lumen (LM)
Normal	M20I-30	300mm [0.98ft]	48VDC	0.11 [0.11A/ft]	5.0 [5.10W/ft]	5.5 [5.61W/ft]	>90	24°	2700K	300
									3000K	310
									3500K	320
									4000K	330
								36°	2700K	300
									3000K	310
									3500K	320
									4000K	330

Note:

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.