

Model: DORCIA BONE C-2(R10) L 59,6X120(A)

Codes: 100355111

Water absorption: Bla - Porcelanico (E<=0.1%)





| DIMENSIONAL FEATURES UNE-EN ISO 10545-2 | | | |
|--|-------------|----------|--|
| Thickness | 8.5 MM | +/-5%* | |
| Width | 596 MM | | |
| Length | 1200 MM | | |
| Length and width deviation | Below 0.15% | +/-0.3%* | |
| Side straightness deviation | Below 0.15% | +/-0.3%* | |
| Squareness deviation | Below 0.15% | +/-0.3%* | |
| Surface flatness deviation | Below 0.15% | +/-0.4%* | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

| MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11 | | |
|--|------------------|------------|
| Breaking strength | 2261.4 N | >1300N* |
| Modulus of rupture | 49.2 N/MM2 | >=35N/mm2* |
| Abrasion resistance | 4 | |
| Crazing resistance | Resists 3 cycles | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

| HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995 | | |
|---|--|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |
| *ISO-13006:2018 UNE-EN 14411:2016 | | |

| ANTI-SLIP VALUE EN 16165: 2022 / ANSI 137 | | |
|--|------------------------|-----------------------|
| Dynamic coefficient of friction | 0.69 (T5C2) | |
| Slip resistance (pendulum-wet) | CL2 | PTV 38* |
| Slip resistance (ramp) | R-10 | 17º TONO 5 / ID 4790* |
| Slip resistance (bare feet) | С | 29º tono 5 - 21282* |
| Pendulum test value (ptv) | WET 45 / DRY 61 (T5C2) | |

^{*}ISO-13006:2018 UNE-EN 14411:2016

System Certification









| PACKING | | |
|------------------------|-------------------|--|
| Sales units per box | 1.430411 M2/BOX | |
| Sales units per pallet | 50.064368 M2/PAL | |
| Sales units per unit | 0.715205 M2/PIECE | |

SCOPE OF USE

Technical code-1 6 - Use on heavy traffic floors

RECOMMENDED USE LOCATIONS

Single-family dwelling

External Premises: External staircases and ramps

Collective housing

Outdoor Premises: Uncovered Terraces (Accessible from outside)

Public Residential

Bathrooms in single or double rooms

Toilets in collective rooms, plant bathroom, office, service rooms maintenance plant

Teacher

Pre-school and Primary: Classroom with direct opening to the exterior

Pre-school and Primary: Playroom, exercise room, multi-purpose room with direct opening to the outside.

Secondary, Baccalaureate and University: Classroom with direct opening to the outside.

Secondary, Baccalaureate and University: Laboratories with aggressive chemicals

Public attendance

Catering: Drinks distribution outlet, automatic machines

Catering: Cooking in small restaurant, bar, cafeteria, cafeteria, company canteen

Entertainment and recreation: Showroom, cinema, theatre, sporting activities, amphitheatres, games (Indoor)

Common transit areas

Indoor premises: Public entrance hall and lifts, in hospital, administrative, public and similar activities.

Indoor premises: Main staircases and heavy duty ramps

Indoor premises: Main staircases and ramps for medium use

Toilets for the public in public, commercial, educational or intensive-use buildings

Toilets for the public in medium-use buildings. Employee toilets

Collective sanitary facilities, changing rooms and showers

Heating, air-conditioning and other humid premises

System Certification





