Model: CANAL CANCUN SAND 59,6X150(A)

Codes: 100354901

Water absorption: BIII - Revestimiento (10%<=E<=20%)



Sistema DAPc® Declaración Ambiental de Productos de Construcción

## DIMENSIONAL FEATURES
UNE-EN ISO 10545-2

| | | |
|---|---|---|
| Thickness | 12.5 MM | +/-5%* |
| Width | 596 MM | |
| Length | 1500 MM | |
| Length and width deviation | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation | Below 0.15% | +/-0.3%* |
| Surface flatness deviation | Below 0.15% | +/-0.4%* |

*ISO-13006:2018 UNE-EN 14411:2016

## MECHANICAL FEATURES
UNE-EN ISO 10545-4-6-7-11

| | |
|---|---|
| Crazing resistance | Resists 3 cycles |

*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES
UNE-EN ISO 10545-13-14:1995

| | | |
|---|---|---|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance | Class 5. Easy cleaning with water | 3 Min.* |

*ISO-13006:2018 UNE-EN 14411:2016

## PACKING

| | | |
|---|---|---|
| Sales units per box | 2.681924 M2/BOX | |
| Sales units per pallet | 48.274629 M2/PAL | |
| Sales units per unit | 0.893975 M2/PIECE | |

## SCOPE OF USE

| | | |
|---|---|---|
| Technical code-1 | 1 - Use on walls | |

System Certification

Do not use cleaning agents containing hydrofluoric acid.
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.
For big sizes, it is recomended to fix with mortars containing polymeric additives and to use the double glueing technique.
Mosaic tiles must be grouted.
This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.