

Model: BOTTEGA CALIZA L 44,3X44,3(A)

Codes: 100325702

Water absorption: Bla - Porcelánico ($E \leq 0.1\%$)



DIMENSIONAL FEATURES

 UNE-EN ISO 10545-2

Thickness	8.5 MM	+/-5%*
Width	443 MM	
Length	443 MM	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

*ISO-13006:2018 UNE-EN 14411:2016

MECHANICAL FEATURES

 UNE-EN ISO 10545-4-6-7-11

Breaking strength	2186 N	>1300N*
Modulus of rupture	43 N/MM2	>=35N/mm2*
Abrasion resistance	4	
Crazing resistance	Resists 3 cycles	

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES

 UNE-EN ISO 10545-13-14:1995

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

*ISO-13006:2018 UNE-EN 14411:2016

ANTI-SLIP VALUE

 EN 16165: 2022 / ANSI 137

Slip resistance (wet pendulum) trrl	CL1	
Slip resistance (shod feet)	R-9/PC6	1689 - TONO 5*
Slip resistance (barefoot)	A/PN12	18131 - Tono 5*
Pendulum test value (ptv) 4s	WET - 24 / DRY - 64 (T7EC2)	

*ISO-13006:2018 UNE-EN 14411:2016

PACKING

Sales units per box	1.373734 M2/BOX	
Sales units per pallet	71.434179 M2/PAL	
Sales units per unit	0.196248 M2/PIECE	

System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

SCOPE OF USE		
Technical code-1	6 - Use on heavy traffic floors	

RECOMMENDED USE LOCATIONS		
Single-family dwelling		
Indoor Premises - Dry: Room, room, bedroom or other enclosure without direct access to the outdoors.		
Collective housing		
Indoor Premises - Residential - Dry: Entrance, living room, dining room, professional office with reception of customers		
Indoor Premises - Housing - Dry: Bedrooms, personal office, storage room, changing room		
Various		
Cladding of bonded or mixed facades		
Facade cladding with mechanical anchors		
Kitchen worktops, bars, restaurants		
Public bathroom countertops		

System Certification

