



## BASIC CHARACTERISTICS:

|              |                                        |
|--------------|----------------------------------------|
| Pieces name: | FLODSTEN SNOW (PRC) 60X120 RC /ARG02_S |
| Size (cm.):  | 60x120                                 |
| Colour:      | SNOW                                   |
| Series name: | FLODSTEN                               |
| Family:      | UNGLAZED PORCELAIN                     |

## TECHNICAL CHARACTERISTICS:

|                                                |                            |                    |
|------------------------------------------------|----------------------------|--------------------|
| Fabrication process:                           | Dry pressed ceramic tile   |                    |
| Absorption group (ISO 13006):                  | BIa                        |                    |
| Finish:                                        | UGL                        |                    |
| Rectified:                                     | Yes                        |                    |
| Body:                                          | Colour Body                |                    |
| Surface Finish:                                | Matt                       |                    |
| Work size (mm):                                | 600 x 1200 x 9             |                    |
| Aesthetic classification and shade variations: | V.3                        |                    |
| Diferent design number:                        | 9                          |                    |
| Facial dimension range and surface quality:    | Complies with the standard | UNE EN ISO 10545-2 |

## PHYSICAL CHARACTERISTICS:

|                   |              |                    |
|-------------------|--------------|--------------------|
| Water absorption: | $E \leq 0.5$ | UNE EN ISO 10545-3 |
|-------------------|--------------|--------------------|

## IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the instalation and grouting visit the Argenta website: [www.argentaceramica.com](http://www.argentaceramica.com). The packing list of this pieces are indicated on the Argenta website: [www.argentaceramica.com/packing-list](http://www.argentaceramica.com/packing-list). The stated weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

## Certifications:





|                                               |                            |                            |
|-----------------------------------------------|----------------------------|----------------------------|
| Braking strength (S):                         | > 1300N                    | UNE EN ISO 10545-4         |
| Flexural tensile strength (N/mm2):            | ≥35 N/mm2                  |                            |
| Lineal thermal expansion between 20° to 100°C | Complies with the standard | UNE EN ISO 10545-8         |
| Thermic shock resistance:                     | Complies with the standard | UNE EN ISO 10545-9         |
| Moisture expansion:                           | Complies with the standard | UNE EN ISO 10545-10        |
| Crazing resistance:                           | Complies with the standard | UNE EN ISO 10545-11        |
| Durability; Freeze - thaw cycle:              | Complies with the standard | UNE EN ISO 10545-12        |
| Scratch hardness according to Mohs:           | 9                          | UNE EN 67-101-92           |
| Slipperiness:                                 | Anti-slip Class 2          | UNE 41901 EX               |
|                                               | Anti-slip R.11             | DIN 51130                  |
|                                               | Anti-slip Class C          | DIN 51097                  |
|                                               | Anti-slip Dcof (>0.42)     | DCOF AcuTest ANSI Standard |
|                                               | +36 Low slip potential     | BS 7976-2:2002 PENDULUM    |
|                                               | Anti-slip P4               | AS 4586-2003               |
| Resistance to Deep abrasion:                  | ≤175 mm3                   | EN ISO 10545-6             |

### CHEMICAL PROPERTIES:

|                                                               |          |                     |
|---------------------------------------------------------------|----------|---------------------|
| Resistance to home cleaning products and swimming pool salts: | Class GA | UNE EN ISO 10545-13 |
| Resistance to High concentration acids and bases:             | HA       |                     |
| Resistance to Low concentration acids and bases:              | LA       |                     |
| Resistance to staining:                                       | Class 5  | UNE EN ISO 10545-14 |

### IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the instalation and grouting visit the Argenta website: [www.argentaceramica.com](http://www.argentaceramica.com). The packing list of this pieces are indicated on the Argenta website: [www.argentaceramica.com/packing-list](http://www.argentaceramica.com/packing-list). The stated weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

Certifications:





## CE MARKING:



004CPR-PR/11-4-2013

## IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed. Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process. For more information about the instalation and grouting visit the Argenta website: [www.argentaceramica.com](http://www.argentaceramica.com). The packing list of this pieces are indicated on the Argenta website: [www.argentaceramica.com/packing-list](http://www.argentaceramica.com/packing-list). The stated weight is approximate, it may vary up to 5% depending on the model, the variation may begreater for products with relief.Document with commercial information and cannot be used either judicially or administratively without the express permission of Argenta Ceramica S.L.The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

## Certifications:

