

Model: GEO DECO MAROON**Codes:** 100350757**Group:** G-213**Format:** 4 221/256"X17 113/256"X3/8" approx.

RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS 25KG
Recommended joint	100236824 COLORSTUK RAPID MOKA N 5KG
Recommended joint (wet area)	100236824 COLORSTUK RAPID MOKA N 5KG
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG

DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES

 Gloss-free	 Material suitable for use on shower walls.
 Material suitable for use on indoor walls.	 Material that features unevenness on the surface.
 There are considerable color changes between pieces.	 Material recommended for installation on walls.

PHYSICAL PROPERTIES

Water absorption	BIII	ISO 10545-2*
Breaking strength	165.3 LBF	>135LBF*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*

CHEMICAL PROPERTIES

Stain resistance	Clase 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*



PACKING

Sales units per box	11.78 SQF/CS
Sales units per pallet	800.9 SQF/PAL
Sales units per unit	0.59 SQF/ST
Sale unit	M2
Base unit	ST
Net weight	331.38 LB/SQF
Gross weight	338.76 LB/SQF



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.