

Model: OLD NATURAL(4P/C) 33,3X100(A)

Codes: 100294988

Water absorption: BIII - Revestimiento ( $10\% \leq E \leq 20\%$ )

Finish: Glazed / Standard

Tone variations: V2

Rectified: Yes



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

|                             |             |          |
|-----------------------------|-------------|----------|
| Thickness                   | 10.5 mm     | +/-5%*   |
| Width                       | 332.8 mm    |          |
| Length                      | 1000 mm     |          |
| Length and width deviation  | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation        | Below 0.15% | +/-0.3%* |
| Surface flatness deviation  | Below 0.15% | +/-0.4%* |

\*ISO-13006:2018 UNE-EN 14411:2016

## FEATURES

- Natural-looking, non-glossy surface finish.
- General deshaded design with a degree of color and appearance variation.
- Name given to the finish of those tiles dimensionally improved after the firing process.
- Finish with clearly defined protrusions that give the surface a feeling of volume.
- Wall installation

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

|                             |                      |                         |
|-----------------------------|----------------------|-------------------------|
| Breaking strength           | 1713 N               | >600N*                  |
| Modulus of rupture          | 28 N/mm <sup>2</sup> | >=12N/mm <sup>2</sup> * |
| Crazing resistance          | Resists 3 cycles     |                         |
| Resistance to thermal shock | RESISTE              |                         |

\*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

|                     |                                                                                                            |         |
|---------------------|------------------------------------------------------------------------------------------------------------|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance    | Class 5. Easy cleaning with water                                                                          | 3 Min.* |

\*ISO-13006:2018 UNE-EN 14411:2016

System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

## ANTI-SLIP VALUE

EN 16165: 2022 / ANSI 137

|                                        |           |
|----------------------------------------|-----------|
| Friction (dry)                         | No Aplica |
| Friction (wet)                         | No Aplica |
| Dynamic coefficient of friction (dcof) | No Aplica |

\*ISO-13006:2018 UNE-EN 14411:2016

## PACKING

|                        |                  |
|------------------------|------------------|
| Sales units per box    | 1.332001 M2/BOX  |
| Sales units per pallet | 58.608059 M2/PAL |
| Sales units per unit   | 0.333 M2/PIECE   |

## SCOPE OF USE

|                  |                  |
|------------------|------------------|
| Technical code-1 | 1 - Use on walls |
|------------------|------------------|

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.