L'ANTIC COLONIAL

Model: TREND V DARK Codes: 100341537 Group: G-213

Format: 12,35X44,3X0,95CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236481 COLORSTUK RAPID ANTRACITA N 5KG	
Recommended joint (wet area)	100236481 COLORSTUK RAPID ANTRACITA N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

	DIMENSION	AL FEATURES
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

FEATURES



Gloss-free



Material suitable for use on indoor walls.



There are considerable color changes between pieces.







Material that features unevenness on the surface.



Material recommended for installation on walls.

	PHYSICAL PROPERTIES	
Water absorption	BIII	ISO 10545-2*
Breaking strength	>900 N	>600N*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*

CHEMICAL PROPERTIES		ERTIES
Stain resistance	Clase 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA/B	ISO 10545-13*





TREND V DARK

L'ANTIC COLONIAL

	PACKING
Sales units per box	1.094203 M2/BOX
Sales units per pallet	74.405797 M2/PAL
Sales units per unit	0.05471 M2/PIECE
Sale unit	M2
Base unit	ST
Net weight	14.933245 KG/M2
Gross weight	15.463311 KG/M2





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

15/07/2025