## L'ANTIC COLONIAL

Model: NEBULA WHITE Codes: 100341501 Group: G-228

Format: 8X30X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236794 COLORSTUK RAPID MARFIL N 5KG	
Recommended joint (wet area)	100236794 COLORSTUK RAPID MARFIL N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

	DIMENSION	AL FEATURES
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

## FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



There are considerable color changes between pieces.



Material recommended for installation on walls.

PHYSICAL PROPERTIES		
Water absorption	BIII	ISO 10545-2*
Breaking strength	>900 N	>600N*
Coefficient of linear thermal expansion	<6.6 1/(10E6*K)	
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*

CHEMICAL PROPERTIES		
Stain resistance	Clase 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*





NERULA WHITE

## L'ANTIC COLONIAL

	PACKING
Sales units per box	0.672 M2/BOX
Sales units per pallet	67.2 M2/PAL
Sales units per unit	0.024 M2/PIECE
Sale unit	M2
Base unit	ST
Net weight	13.541667 KG/M2
Gross weight	13.916667 KG/M2





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

15/07/2025