

Model: VERTICE SAVANNAH ACERO 59,6X150(A)

Codes: 100330322

Water absorption: BIII - Revestimiento ( $10\% \leq E \leq 20\%$ )

Finish: Glazed / Standard

Tone variations: V2

Rectified: Yes



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

|                             |             |          |
|-----------------------------|-------------|----------|
| Thickness                   | 10.5 mm     | +/-5%*   |
| Width                       | 596 mm      |          |
| Length                      | 1500 mm     |          |
| Length and width deviation  | Below 0.15% | +/-0.3%* |
| Side straightness deviation | Below 0.15% | +/-0.3%* |
| Squareness deviation        | Below 0.15% | +/-0.3%* |
| Surface flatness deviation  | Below 0.15% | +/-0.4%* |

\*ISO-13006:2018 UNE-EN 14411:2016

## FEATURES

- Natural-looking, non-glossy surface finish.
- General deshaded design with a degree of color and appearance variation.
- Name given to the finish of those tiles dimensionally improved after the firing process.
- Finish with clearly defined protrusions that give the surface a feeling of volume.
- Wall installation

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

|                    |                       |                         |
|--------------------|-----------------------|-------------------------|
| Breaking strength  | >600 N                | >600N*                  |
| Modulus of rupture | >15 N/mm <sup>2</sup> | >=12N/mm <sup>2</sup> * |
| Crazing resistance | Resists 3 cycles      |                         |

\*ISO-13006:2018 UNE-EN 14411:2016

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14:1995

|                     |                                                                                                            |         |
|---------------------|------------------------------------------------------------------------------------------------------------|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance    | Class 5. Easy cleaning with water                                                                          | 3 Min.* |

\*ISO-13006:2018 UNE-EN 14411:2016

## PACKING

|                        |                   |  |
|------------------------|-------------------|--|
| Sales units per box    | 2.681924 M2/BOX   |  |
| Sales units per pallet | 53.638477 M2/PAL  |  |
| Sales units per unit   | 0.893975 M2/PIECE |  |

System Certification



| SCOPE OF USE     |                  |  |
|------------------|------------------|--|
| Technical code-1 | 1 - Use on walls |  |

System Certification

