

Model: PARMA LEATHER  
Codes: 100321923  
Group: G-226  
Format: 8X30X0,85CM



| RECOMMENDATIONS                 |                                       |  |
|---------------------------------|---------------------------------------|--|
| Recommended adhesive            | 100043280 TIXOCEM PLUS 25KG           |  |
| Recommended joint               | 100236808 COLORSTUK RAPID BEIGE N 5KG |  |
| Recommended joint (wet area)    | 100236808 COLORSTUK RAPID BEIGE N 5KG |  |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS 25KG           |  |

| DIMENSIONAL FEATURES        |        |                     |
|-----------------------------|--------|---------------------|
| Length and width deviation  | ±0.5%  | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.3 % | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | ±0.5%  | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | ±0.5 % | UNE-EN ISO 10545-2* |

| FEATURES                                                                                                                            |                                                                                                                                        |
|-------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
|  Gloss-free                                      |  Material suitable for use on shower walls.         |
|  Material suitable for use on indoor walls.      |  There are consistent color changes between pieces. |
|  Material recommended for installation on walls. |                                                                                                                                        |

| PHYSICAL PROPERTIES |         |               |
|---------------------|---------|---------------|
| Water absorption    | BIII    | ISO 10545-2*  |
| Breaking strength   | >900 N  | >600N*        |
| Crack resistance    | PASS    | ISO 10545-11* |
| Flammability        | A1      | EN 13501-1*   |
| Flexural strength   | >20 MPA | ISO 10545-4*  |

| CHEMICAL PROPERTIES     |            |               |
|-------------------------|------------|---------------|
| Stain resistance        | Clase 5    | ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA | ISO 10545-13* |



| PACKING                |                 |  |
|------------------------|-----------------|--|
| Sales units per box    | 0.672 M2/BOX    |  |
| Sales units per pallet | 67.2 M2/PAL     |  |
| Sales units per unit   | 0.024 M2/PIECE  |  |
| Sale unit              | M2              |  |
| Base unit              | ST              |  |
| Net weight             | 14.333333 KG/M2 |  |
| Gross weight           | 14.666667 KG/M2 |  |

