## L'ANTIC COLONIAL

Model: CLASSIC 1L HERRINGBONE GREY

Codes: 100286590 Group: G-244

Format: 13X72,5X1,4CM



## **ADDITIONAL NOTES**

This material may contain some pieces with sapwood. Although the color of the skirting boards, profiles and step borders may vary according to the model, the color will be as similar as possible to that of the wood floor.

COMPOSITION						
		Size	Material	Type of material		
	Layer 1	0.060-0.070	Varnish	APRESTO MATTE		
	Layer 2	2.5	Hardwood Layer	Oak wood		
	Layer 3	9.5	Intermediate Layer	PINE		
	Layer 4	2.0	Backside	PINE		

TOLERANCES						
Squareness of the item	0.2% of width.					
Difference in height among items	0.2					
Curvature	0.1% of length.					

LABORATORY TESTS						
Thermal conductivity	0.14 W/M*K	UNE-EN 12667:2002*				
Heat resistance	0.103 M2*K/W	UNE-EN 12667:2002*				
Formaldehyde emissions	0.024 mg/m3	EN - 717/1:2006*				
Moisture content	7% +/-2%	UNE-EN 13183-1 / AC:2004*				
Flammability	Dfl-S1	UNE EN 13501-1:2007*				
Bulk density	min 500kg/m3	UNE-EN 323:1994*				
Slip resistance (wet pendulum) irhd 55	CL 2 (40)	EN 16165 Anexo C*				
Slip resistance (pendulum-dry)	65	EN 16165 Anexo C*				
Dynamic coefficient of friction (dcof)	0.63	ANSI A137.1*				





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

28/08/2025

## L'ANTIC COLONIAL

## **FEATURES**



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



Slight smoothing of the wood using a brush to achieve a surface with a slight



Applying a color oil or varnish on the wood surface in order to get different color  $\,$ 



Beveled cut on all 4 edges of the board for emphasizing size



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.





Format where only one board has been used to finish the entire base surface



Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered



It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



Made with oak wood.



There are consistent color changes between pieces.

Is suitable for installing on water radiant heating



Material from a European country.



Independent (non-governmental) certificate that guarantees consumers that forest products come from rationally exploited forests



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



2.5 mm





Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

_	,
	ς.
KK	. 1
VA I	7)
VIX	//

It is necessary to apply adhesive for installing it.

	PACKING
Sales units per box	0.65975 M2/BOX
Sales units per pallet	42.224 M2/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	9.145889 KG/M2
Gross weight	9.665782 KG/M2

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100298245	IGUALACION CLASSIC HERRINGBONE GREY 4,5	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100298265	TRANSICION CLASSIC HERRINGBONE GREY4X270	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100298272	ZOCALO CLASSIC HERRINGBONE GREY 8X220	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.