L'ANTIC COLONIAL

Model: LUTIER 1L MARRON

Codes: 100272992 Group: G-235

Format: 18X220X1,4CM



ADDITIONAL NOTES

This material may contain some pieces with sapwood. For a better use of wood, any natural wood order may contain a percentage of half boards, between 15% and 30%, depending on the model. Although the tone of the skirting boards, profiles and stair nosings may vary, depending on the model, the color will be as similar as possible to that of the wood floor.

COMPOSITION						
		Size	Material	Type of material		
	Layer 1	0.060-0.070	Oil			
	Layer 2	2.5	Hardwood Layer	Ash wood		
	Layer 3	9	Intermediate Layer	PINE		
	Layer 4	2.5	Backside	PINE		

TOLERANCES					
Squareness of the item	0.2% of width.				
Difference in height among items	0.2 mm				
Curvature	0.1% of length.				

LABORATORY TESTS						
Thermal conductivity	0.14 W/M*ºK W/M*K	UNE-EN 12667:2002**				
Heat resistance	0.103 M2*ºK/W M2*K/W	UNE-EN 12667:2002**				
Formaldehyde emissions	0.011 ±0.001 mg/m3	EN-717/1:2006** UNE EN 13501-1:2007**				
Flammability	Dfl-S1					
Bulk density	min 500Kg/m3	UNE-EN 323:1994**				
Slip resistance (wet pendulum) irhd 55	CL 1 (36)	EN 16165 Anexo C*				
Slip resistance (pendulum-dry)	45	EN 16165 Anexo C*				
Dynamic coefficient of friction (dcof)	0.51	ANSI A137.1*				





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

28/08/2025

L'ANTIC COLONIAL

FEATURES



It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Combination of oils and waxes prepared for drying with UV lamps. With this finish, wood preserves the natural look of conventional oil but is more resistant to stains from everyday-use products and needs less maintenance. Advantages: Very natural look, low maintenance, and greater resistance to stains from water, wine, juice... Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Is suitable for installing on water radiant heating



Format where only one board has been used to finish the entire base surface



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with outty.



It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.





There are considerable color changes between pieces.



Material from a European country.

Made from ash wood.



Independent (non-governmental) certificate that guarantees consumers that forest products come from rationally exploited forests



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



2.5 mm

Sales units per box Sales units per pallet

Sales units per square meter



lower plywood that provides dimensional stability.

It is necessary to apply adhesive for installing it.



Sale unit

Base unit
Net weight

Gross weight

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

2.772 M2/BOX

8.936869 KG/M2

9.376263 KG/M2

1 M2

M2

ST

PACKING	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100272936	IGUALACION LUTIER MARRON 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100273000	MAMPERLAN LUTIER 1L MARRON 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100272954	TRANSICION LUTIER MARRON 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100272968	ZOCALO LUTIER MARRON 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.83 KG/PIECES	1.91 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

28/08/2025