L'ANTIC COLONIAL

Model: GENOVA 1L CHROME

Codes: 100316291 Group: G-246

Format: 218X14,5X1,4CM



ADDITIONAL NOTES

This material may contain some pieces with sapwood. For a better use of wood, any natural wood order may contain a percentage of half boards, between 15% and 30%, depending on the model. Although the tone of the skirting boards, profiles and stair nosings may vary, depending on the model, the color will be as similar as possible to that of the wood floor.

COMPOSITION						
		Size	Material	Type of material		
	Layer 1	0.060-0.070	Varnish	Apresto Mate treatment		
	Layer 2	3	Hardwood Layer	Oak wood		
	Layer 3	9	Intermediate Layer	Wood or HDF slats		
	Layer 4	2	Backside	Coniferous wood		

	TOLERANCES	
Width of face	±0.2 mm	
Curvature	0.1% of length.	

LABORATORY TESTS						
Resistance to abrasion	≥500	UNE-EN 13696:2009*				
Mass per surface	10.95 KG/M2	EN 14342*				
Thermal conductivity	0.18 W/M*K	UNE-EN 12667:2002*				
Heat resistance	0.08 M2*K/W	UNE-EN 12667:2002*				
Formaldehyde emissions	E1	EN 717*				
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*				
Flammability	Cfl-s1	EN 13501*				
Bulk density	782 Kg/m3	UNE-EN 323:1994*				
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*				
Slip resistance (wet pendulum) irhd 55	CL 1 (30)	EN 16165 Anexo C*				
Slip resistance (pendulum-dry)	50	EN 16165 Anexo C*				
Dynamic coefficient of friction (dcof)	0.51	ANSI A137.1*				





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

28/08/2025

L'ANTIC COLONIAL

FEATURES



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



Slight smoothing of the wood using a brush to achieve a surface with a slight



Applying a color oil or varnish on the wood surface in order to get different color



Beveled cut on all 4 edges of the board for emphasizing size



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be acrificely learned. be easily cleaned.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by ${\tt L}'$ Antic Colonial.



Is suitable for installing on water radiant heating



Material with few knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



Made with oak wood.



There are consistent color changes between pieces.



Material from a North American country.



Material from a European country.



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests





It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

PACKING					
Sales units per box	2.2127 M2/BOX				
Sales units per pallet	108.4223 M2/PAL				
Sales units per square meter	1 M2				
Sale unit	M2				
Base unit	ST				
Net weight	11.777918 KG/M2				
Gross weight	12.227143 KG/M2				

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100316282	IGUALACION GENOVA CHROME 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100316283	MAMPERLAN GENOVA 1L CHROME 120X7X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100316300	TRANSICION GENOVA CHROME 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100316297	ZOCALO GENOVA CHROME 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

28/08/2025 2/2