

Model: AC4 STYLE 1L BREATHE

Codes: 100289653

Group: G-204

Format: 19,2X126,1X0,7CM



COMPOSITION



	Size	Material	Type of material
Layer 1	0.2	Melamine	Aminoplastic thermosetting resins
Layer 2	0.1	Decorative paper	
Layer 3	6.6	HDF	High-density Fiber Board and water-repellent glues
Layer 4	0.1	Backside	Sheets of kraft paper impregnated with phenolic resins

FEATURES



Imitates the surface of wood

20

20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Format where only one board has been used to finish the entire base surface



Environmental Product Declarations for Construction (DAPcons®) are an essential instrument for environmental improvement in the construction sector and, therefore, a useful tool for technicians, manufacturers and users. DAPcons® certifications cover products from the different stages of a building. They provide objective, agreed and verified information on a product.



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



32. General commercial



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

5

5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Is suitable for installing on water radiant heating



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



23. Intensive residential



Abrasion-resistance level as per Standard UNE-EN 13329

It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places, this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

28/08/2025

1/2

DIMENSIONAL FEATURES		
Item thickness	≤0.50 mm	EN 13329*
Length of face	0.50 mm	EN 13329*
Width of face	△medios≤0.10 medio/máx-min≤0.20 mm	EN 13329*
Squareness of the item (q)	≤0.20 mm	EN 13329*
Straightness of face	≤0.30 mm/M	EN 13329*
Flatness of item (f)	fw cóncavo≤0.15/fw convexo≤0.20/fl cóncavo≤0.50/fl convexo≤1.00 %	EN 13329*
Joint between items	medios≤0.15/máx≤0.20 mm	EN 13329*
Difference in height among items	Max≤0.15 Prom≤0.10 mm	EN 13329*
Dimensional variations related to changes in relative moisture	medios≤0.9 mm	EN 13329*
Uv light fastness	7	EN 438-2,16*
Surface stripping	≥1.25 N/mm2	EN 13329 Anexo D*

LABORATORY TESTS		
Resistance to abrasion	AC4	UNE EN 13329:2000*
Impact resistance	(Bola grande) (Bola pequeña) 750/≥35	EN 13329*
Resistance to staining	Grado 5 (G 1 y 2) y Grado 4 (G 3)	EN 438-2.15*
Resistance to cigarette burns	4	EN 438*
Swelling in thickness	≤18 %	UNE-EN 13329*
Moisture upon leaving factory	4%-10%	
Formaldehyde emissions	E1	EN 717-1*
Slip resistance (wet pendulum) irhd 55	CL 1 (29)	EN 16165 Anexo C*
Tensile strength of joints	>1.0 kN/m	EN 13329*
Fire resistance	Cfl-s1	EN 13501*
Heat resistance	0.046 m2 K/W	ISO 8302*
Thermal conductivity	0.174 W/M*K	
Dynamic coefficient of friction (dcof)	0.56	ANSI A137.1*
Critical radiant flux	Class I	ASTM E648*
Density of the board	914 kg/m3-6.4 kg/m2	UNE EN 323*
Slip resistance (pendulum-dry)	CL 3 (55)	EN 16165 Anexo C*

PACKING		
Sales units per box	2.42112 M2/BOX	
Sales units per pallet	125.898238 M2/PAL	
Sales units per unit	0.242112 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	6.633294 KG/M2	
Gross weight	6.810898 KG/M2	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100297563	IGUALACION STYLE BREATHE 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.8 KG/PIECES
100297593	MAMPERLAN AC4 STYLE 1L BREATHE 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100297548	TRANSICION STYLE BREATHE 4X270X1	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.8 KG/PIECES
100297549	ZOCALO STYLE BREATHE 8X225X1,4	G-107	12 PIECES/BOX	648 PIECES/PAL	5.56 PIECES/M2	-	-	1.57 KG/PIECES	1.62 KG/PIECES

