L'ANTIC COLONIAL

Model: LINKFLOOR SUPREME BROWN

Codes: 100330816 Group: G-228

Format: 23X226X0,75CM



COMPOSITION Size Material Type of material Layer 1 0.7 Wear layer Use layer with PU protection Layer 2 decorative film 5.7 Laver 3 SPC core IXPE motherboard IXPE Layer 4

ADDITIONAL NOTES

COMPOSITION: Engineered SPC Enhanced Resilent Multi-Layer Vinyl Plank / Tile

FEATURES



Imitates the surface of wood



Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.



25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Floor capable of dissipating excess electrical charges and distribute them over its



There are consistent color changes between pieces.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



10 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Is suitable for installing on water radiant heating



It is a quick and easy installation system. Adjust the slat to be installed lengthwise to the one already placed and tap it lightly with a rubber hammer and block. It is just as easy to uninstall, which allows it to be quickly dismantled.





L'ANTIC COLONIAL

	LABORATORY TESTS				
Commercial area class	34	EN 10582*			
Slip resistance (shod feet)	R-9	EN 16165 Anexo B*			
Abrasion resistance	≥6000	EN 13329*			
Impact resistance	2000 mm/45 N	EN 438-2*			
Resistance to staining	GRUPO 1 y 2: GRADO 5 GRUPO3: GRADO 4	EN 438-2*			
Swelling in thickness	≤12 %	ISO 24336*			
Dimensional stability	LD:-0.13%/MD: 0.11%	ISO 23999*			
Resistance to microscratching	MSR-A1/MSR-B1	EN 16094*			
Formaldehyde emissions	E1	EN 14041 EN 717-1*			
Slip resistance (wet pendulum) irhd 55	CL 1 (24)	EN 16165 Anexo C*			
Tensile strength of joints	Longitudinal=3.6 kN/m; Transversal=2.7 kN/m	ISO 24334*			
Fire resistance	Bfl-S1	EN 13501*			
Evaluation of propensity to accumulation of electrostatic charges	0.81 KV	EN 1815*			
Heat resistance	0.047 M2*K/W	EN 12667*			
Thermal conductivity	0.161 W/M*K	EN 12664*			
Uv light fastness	≥Grado 6	ISO 105*			
Residual footprint	0.04 mm	EN ISO 24343-1*			
Acoustic insulation	Ln,w=43 dB;Rw=67 dB ; ΔLw=19 dB	ISO 717-2 ; ISO 717-1*			
Dynamic coefficient of friction (dcof)	0.63	ANSI A137.1*			
Residual footprint	≤0.1 mm	*			
Residual footprint	0.07				
Resistance to chemicals	PASS	EN ISO 26987*			
Private area class	23	EN 10582*			
Slip resistance (pendulum-dry)	83	EN 16165 Anexo C*			

	PACKING
Sales units per box	1.5594 M2/BOX
Sales units per pallet	70.173 M2/PAL
Sales units per unit	0.5198 M2/PIECE
Sale unit	M2
Base unit	ST
Sales units per square meter	1 M2
Net weight	14.459407 KG/M2
Gross weight	15.151982 KG/M2

SPECIAL PIECES											
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight		
100257147	PERFIL ADH LINKFLOOR ALUMINIO 3,5X270	G-121	40 PIECES/BOX	1000 PIECES/PAL	10.58 PIECES/M2	-	-	0.37 KG/PIECES	0.39 KG/PIECES		
100330850	PERFIL ADH LINKFLOOR SUPREME BROWN 3,5	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.8 KG/PIECES		
100346320	ZOCALO LINKFLOOR PVC SUPREME BROWN 8X223	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	=	1.1 KG/PIECES	1.25 KG/PIECES		





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

29/08/2025