


Model: LINKFLOOR HARMONY NATURAL
Codes: 100366822
Group: G-222
Format: 22,8X152,4X0,6CM



COMPOSITION



	Size	Material	Type of material
Layer 1	0,5	Wear layer	
Layer 2	0,1	Vinyl	decorative film
Layer 3	4,4	SPC	SPC core
Layer 4	1	IXPE	IXPE motherboard

FEATURES

- 

Imitates the surface of wood
- 

Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.
- 

25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
- 

Floor capable of dissipating excess electrical charges and distribute them over its entire surface
- 

There are consistent color changes between pieces.
- 

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- 

10 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
- 

Is suitable for installing on water radiant heating
- 

Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
- 

Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.

LABORATORY TESTS

Commercial area class	33	EN 10582*
Dimensional stability	0.25 %	ISO 23999*
Resistance to microscratching	MSR-A3/MSR-B1	EN 16094*
Formaldehyde emissions	E1	EN 717-1*
Slip resistance (wet pendulum) irhd 55	CL 2 (40)	EN 16165 Anexo C*
Fire resistance	Bfl-S1	EN 13501*
Fire resistance	CLASS A	ASTM E84*
Heat resistance	0.0311 M2*K/W	EN 12667*
Thermal conductivity	0.296 W/M*K	EN 12667*
Dynamic coefficient of friction (dcof)	0.47	ANSI 137.1*
Private area class	23	EN 10582*



PACKING		
Sales units per box	2.432304 M2/BOX	
Sales units per pallet	97.292159 M2/PAL	
Sales units per unit	0.347472 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	10.835406 KG/M2	
Gross weight	11.333287 KG/M2	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100366828	MAMPER LINKFLOOR HARMONY NATURAL 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100366872	PERF. ADH. LINKFLOOR HARMONY NATURAL 4	G-155	30 PIECES/BOX	3000 PIECES/PAL	10 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100257147	PERFIL ADH LINKFLOOR ALUMINIO 3,5X270	G-121	40 PIECES/BOX	1000 PIECES/PAL	10.58 PIECES/M2	-	-	0.37 KG/PIECES	0.39 KG/PIECES
100366803	ZOCALO LINKFLOOR PVC HARMONY NATURAL 8	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.1 KG/PIECES	1.25 KG/PIECES
100343146	ZOCALO PVC PAPEL BLANCO 8X223X1,5	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.41 KG/PIECES	1.49 KG/PIECES

