


Model: LINKFLOOR FEUDAL BROWN


Codes: 100298311

Group: G-222

Format: 22,8X152X0,5CM



COMPOSITION



	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	decorative film
Layer 3	3.4	SPC	SPC core
Layer 4	1.0	IXPE	Foam

FEATURES

 Imitates the surface of wood

 Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.

5

5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.

 Floor capable of dissipating excess electrical charges and distribute them over its entire surface

 There are consistent color changes between pieces.

 Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

25

25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.

 Is suitable for installing on water radiant heating

 It is a quick and easy installation system. Adjust the slat to be installed lengthwise to the one already placed and tap it lightly with a rubber hammer and block. It is just as easy to uninstall, which allows it to be quickly dismantled.

DIMENSIONAL FEATURES

Squareness of the item (q)	≤ 400 mm ≤0,25 mm >400 mm ≤0,35 mm	
Difference in height among items	≤0.2 mm	ISO 10582*



LABORATORY TESTS		
Commercial area class	33	EN 10582*
Slip resistance (shod feet)	R-10	EN 16165 Anexo B*
Abrasion resistance	CLASE T	EN 660-1,2*
Impact resistance	PASS	EN 438-2*
Swelling in thickness	0.16 %	ISO 24336*
Dimensional stability	LD: 0.04%/MD:-0.2%	ISO 23999*
Resistance to microscratching	MSR-A1/MSR-B1	EN 16094*
Formaldehyde emissions	E1	EN 717-2*
Slip resistance (wet pendulum) irhd 55	CL 2 (41)	EN 16165 Anexo C*
Tensile strength of joints	Longitudinal=4.4 kN/m; Transversal=4.3 kN/m	ISO 24334*
Fire resistance	Bfl-S1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	0.4 KV	EN 14021/ EN 1815*
Heat resistance	0.030 M2*K/W	UNE-EN 12667:2002*
Thermal conductivity	0.126 W/(m.k) W/M*K	UNE-EN 12667:2002*
Uv light fastness	>Grado 6	ISO 105*
Curvature	0.11 mm	ISO 23999*
Acoustic insulation	IIC=56 dB;STC=50 dB ; ΔIIC=23 dB	ASTM E90; ASTM E492*
Dynamic coefficient of friction (dcof)	0.47	ANSI 137.1*
Resistance to chemicals	PASS (CLASE 0)	ISO 26987*
Private area class	23	EN 10582*
Slip resistance (pendulum-dry)	80	EN 16165 Anexo C*

PACKING		
Sales units per box	2.772476 M2/BOX	
Sales units per pallet	133.078855 M2/PAL	
Sales units per unit	0.34656 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Sales units per square meter	1 M2	
Net weight	8.841194 KG/M2	
Gross weight	9.207654 KG/M2	

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100312756	MAMPER LINKFLOOR FEUDAL BROWN 7X120	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100312761	PERFIL ADH LINKFLOOR FEUDAL BROWN 3,5	G-155	20 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	0.77 KG/PIECES	0.8 KG/PIECES
100346304	ZOCALO LINKFLOOR PVC FEUDAL BROWN 8X223	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.1 KG/PIECES	1.25 KG/PIECES

