


Model: LINKFLOOR KINGDOM GREECE  
Codes: 100245970  
Group: G-227  
Format: 22,8X180X0,55CM





|         | Size | Material    | Type of material             |
|---------|------|-------------|------------------------------|
| Layer 1 | 0.5  | Wear layer  | Use layer with PU protection |
| Layer 2 | 0.1  | Vinyl       | decorative film              |
| Layer 3 | 0.7  | Elastic PVC | Intermediate comfort layer   |
| Layer 4 | 3.2  | SPC         | SPC composite body           |
| Layer 5 | 1    | IXPE        | IXPE motherboard             |

Floorscore certification

FLOORSCORE

ADDITIONAL NOTES

COMPOSITION: Engineered SPC Enhanced Resilient Multi-Layer Vinyl Plank / Tile

FEATURES

Imitates the surface of wood

Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.

25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.

Floor capable of dissipating excess electrical charges and distribute them over its entire surface

There are consistent color changes between pieces.

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

10 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.

Is suitable for installing on water radiant heating

Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.

DIMENSIONAL FEATURES

|                            |        |             |
|----------------------------|--------|-------------|
| Squareness of the item (q) | 0.07 % | ASTM F2199* |
| Straightness of face       | 0.13 % | ASTM F2199* |



| LABORATORY TESTS                                                  |                                                                                                         |                                                 |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| Commercial area class                                             | 33                                                                                                      | EN 10582*                                       |
| Slip resistance (shod feet)                                       | R-10                                                                                                    | EN 16165 Anexo B*                               |
| Abrasion resistance                                               | CLASE T                                                                                                 | EN660-1*                                        |
| Impact resistance                                                 | PASS                                                                                                    | EN 433*                                         |
| Formaldehyde emissions                                            | E1                                                                                                      | EN 717-2*                                       |
| Slip resistance (wet pendulum) irhd 55                            | CL 2 (41)                                                                                               | EN 16165 Anexo C*                               |
| Tensile strength of joints                                        | Longitudinal=7.6 kN/m; Transversal=8.9 kN/m                                                             | ISO 24334*                                      |
| Fire resistance                                                   | Bfl-S1                                                                                                  | EN 13501*                                       |
| Fire resistance                                                   | CLASS A                                                                                                 | ASTM E84*                                       |
| Evaluation of propensity to accumulation of electrostatic charges | 0.5 kV                                                                                                  | EN 14021/ EN 1815*                              |
| Heat resistance                                                   | 0.052 M2*K/W                                                                                            | EN 12667*                                       |
| Thermal conductivity                                              | 0.108 W/M*K                                                                                             | EN 12667*                                       |
| Uv light fastness                                                 | >Grado 6                                                                                                | ISO 105*                                        |
| Residual footprint                                                | 0.06 mm/1%                                                                                              | EN ISO 24343-1*                                 |
| Acoustic insulation                                               | (6"): IIC=54 dB;STC=51 dB/(7"): IIC=59 dB;STC=54 dB/(8"): IIC=57 dB;STC=52dB/(OWT): IIC=57 dB;STC=61 dB | ASTM E492 ; ASTM E90**                          |
| Flexibility                                                       | PASS                                                                                                    | ASTM F137-08(2013)*                             |
| Dynamic coefficient of friction (dcof)                            | 0.55                                                                                                    | ANSI 137.1*                                     |
| Critical radiant flux                                             | 1.08 W/CM2 (CLASS I)                                                                                    | ASTM E648*                                      |
| Residual footprint                                                | 0.00 mm/0%                                                                                              | ASTM F970-15*                                   |
| Residual footprint                                                | 0.03 mm/0.6%                                                                                            | ASTM F1914-07*                                  |
| Residual footprint                                                | 0.22 mm/4%                                                                                              | ASTM F970-17 extended 1000 PSI [≤0.5 mm / ≤9%]* |
| Resistance to chemicals                                           | PASS (CLASS 0)                                                                                          | ASTM F925*                                      |
| Private area class                                                | 23                                                                                                      | EN 10582*                                       |
| Slip resistance (pendulum-dry)                                    | 80                                                                                                      | EN 16165 Anexo C*                               |

| PACKING                      |                 |  |
|------------------------------|-----------------|--|
| Sales units per box          | 2.4624 M2/BOX   |  |
| Sales units per pallet       | 137.8944 M2/PAL |  |
| Sales units per unit         | 0.4104 M2/PIECE |  |
| Sale unit                    | M2              |  |
| Base unit                    | ST              |  |
| Sales units per square meter | 1 M2            |  |
| Net weight                   | 9.980507 KG/M2  |  |
| Gross weight                 | 10.331384 KG/M2 |  |

| SPECIAL PIECES |                                          |       |               |                 |                 |     |            |                |                |
|----------------|------------------------------------------|-------|---------------|-----------------|-----------------|-----|------------|----------------|----------------|
| SAP            | Description                              | Group | Boxes         | Pallet          | Units           | SKU | Basic Unit | Net Weight     | Gross weight   |
| 100264739      | MAMPER LINKFLOOR KINGDOM GREECE 7X120    | G-163 | 2 PIECES/BOX  | 200 PIECES/PAL  | 11.9 PIECES/M2  | -   | -          | 1.58 KG/PIECES | 1.64 KG/PIECES |
| 100257147      | PERFIL ADH LINKFLOOR ALUMINIO 3,5X270    | G-121 | 40 PIECES/BOX | 1000 PIECES/PAL | 10.58 PIECES/M2 | -   | -          | 0.37 KG/PIECES | 0.39 KG/PIECES |
| 100245916      | PERFIL ADH LINKFLOOR KINGDOM GREECE 3,5  | G-155 | 20 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2  | -   | -          | 0.77 KG/PIECES | 0.8 KG/PIECES  |
| 100128267      | ZOCALO ALUMINIO 8X225                    | G-121 | 12 PIECES/BOX | 696 PIECES/PAL  | 5.56 PIECES/M2  | -   | -          | 1.57 KG/PIECES | 1.62 KG/PIECES |
| 100346307      | ZOCALO LINKFLOOR PVC KINGDOM GREECE8X223 | G-113 | 12 PIECES/BOX | 648 PIECES/PAL  | 5.61 PIECES/M2  | -   | -          | 1.1 KG/PIECES  | 1.25 KG/PIECES |

