



OAK SCURRO

The dark brown hues in this smoked, single-strip oak floor from the Domani Collection highlight its rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	151XCDEKWFKW195 / 7393969045360	range		
Design / Wood Species	Plank / Oak	Warranty	30 years	
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES	•	
Natural/Stained		-	FN13183	70/ + 20/
Design features	Handscraped, Microbevelled 4-sided, Smoked	Moisture content	EN13183	7%±2%
Width x Length x Thickness	190 x 1900 x 15 mm	- Minimun Mean Density - kg/m³		>500 kg/m³
Weight per package / per	17.1 kg / 7.77 kg	Reaction To Fire	EN13501-1	Dfl-s1
m2		- Formaldehyde Emission	FN717-1	F1
Area per package	2.17 m ²	- Content PCP	CFN/TR14823	
Grading	Dynamic		EN1533	≤ 5 ppm NPD
Joint	Woodloc® 5G	- Breaking Strength N/mm ²	EN12664	
Installation method	Floating, Glue-down	Thermal Conductivity		0,11W/mK
Floor heating	Yes	Biological Durability	EN350-2	Class 1
Wear leayer material /	Hardwood / 3.5 mm	- CARB2	65N #645 676	Compliant
thickness		Slip resistance	CEN/TS15676	NPD
Resandable	2-3 times	TSCA BUSSION CLASS	Gressions dams liver retributur-	
Core material	Spruce	CARB P2		
Backside material	Veneer	Compliant Salvw on BASIA	Α	

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

