



OAK FREDRIK

Oak Fredrik is a true rustic product where the surface is handcrafted and deeply brushed to enhance the beauty and specific characteristics of each and every board. The product is smoked which gives the floor a dark brown color and big color variations. Nature oil finished. This product must be oiled after installation and prior to use.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer engineered	
Article Number / EAN Code	151N7BEKFCKW240 / 7393969036047	
Design / Wood Species	1-strip / White Oak	
Surface Treatment /	Oil / Natural	
Natural/Stained		
Refining Treatment	Beveled 4-sided, Handscraped, Brushed,	
	Smoked	
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"	
Weight per package / per	48.5 lbs / 18 lbs	
m2		
Area per package / per	29.3 sqft / 1317.5 sqft	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-Down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 1/8"	
thickness		
Resandable	2 times	
Core material	Pine/Spruce	
Backside material	Hardwood	

PRODUCT DETAILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	_
range		
Warranty	25 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
- Slip resistance	CEN/TS15676	NPD











DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

