



## OAK NOUVEAU GREIGE

The lightly smoked, grey-stain found on this single-strip oak floor from the Classic Nouveau Collection enhance the earth undertones and balance the natural contrasts in the wood. Knots and cracks lightly pepper the boards, adding subtle depth to the floor's elegant expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

| PRODUCT DETAILS             |  |  |
|-----------------------------|--|--|
| Product type / Construction | Wood Floors / 3-layer parquet                |  |
| Article Number / EAN Code   | 151N8AEKGGKW220 / 7393969041195              |  |
| Design / Wood Species       | Plank / Oak                                  |  |
| Surface treatment /         | Matt lacquer / Stained                       |  |
| Natural/Stained             |  |  |
| Design features             | Microbevelled 4-sided, Brushed, Light smoked |  |
| Width x Length x Thickness  | 187 x 2266 x 15 mm                           |  |
| Weight per package / per    | 21 kg / 8.4 kg                               |  |
| m2                          |  |  |
| Area per package / per      | 2.54 m <sup>2</sup> / 114.3 m <sup>2</sup>   |  |
| pallet                      |  |  |
| Grading                     | Lively                                       |  |
| Joint                       | Woodloc® 5S                                  |  |
| Installation method         | Floating, Glue-down                          |  |
| Floor heating               | Yes  |  |
| Wear leayer material /      | Hardwood / 3.5 mm                            |  |
| thickness                   |  |  |
| Resandable                  | 2-3 times                                    |  |
| Core material               | Pine/Spruce                                  |  |
| Hardness (Brinell) value /  | 3,7 / 2.2 - 5.9                              |  |
| range                       |  |  |

| PRO | DUCT | DETAILS |
|-----|------|---------|
|     |      |         |

| Warranty                            | 30 years    |            |
|-------------------------------------|-------------|------------|
| TECHNICAL PROPERTIES                | 5           |            |
| Moisture content                    | EN13183     | 7%±2%      |
| Minimun Mean Density                |             | >500 kg/m³ |
| kg/m³                               |             |            |
| Reaction To Fire                    | EN13501-1   | Dfl-s1     |
| Formaldehyde Emission               | EN717-1     | E1         |
| Content PCP                         | CEN/TR14823 | ≤ 5 ppm    |
| Breaking Strength N/mm <sup>2</sup> | EN1533      | NPD        |
| Thermal Conductivity                | EN12664     | 0,11W/mK   |
| Biological Durability               | EN350-2     | Class 1    |
| CARB2                               |             | Compliant  |
| Slip resistance                     | CEN/TS15676 | NPD        |



















## **DETAILED DESCRIPTION**

DDODLICT DETAILS

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection



OAK NOUVEAU WHISPER



OAK NOUVEAU LACE



OAK NOUVEAU RICH



OAK NOUVEAU BLONDE



OAK NOUVEAU GRAY



OAK NOUVEAU TAWNY



OAK NOUVEAU GREIGE



OAK NOUVEAU WHITE



OAK NOUVEAU SNOW