



OAK CONCRETE

ODLICT DETAIL O

The natural oil finish and sleek grey stain found on this single-strip oak floor from the Artisan Collection create a refined yet rustic expression. Knots and cracks pepper the boards, adding depth and balancing the bleached wheat highlights. Every board is carefully brushed to bring out the character of the grain and emphasise the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	151YCDEKFMKW195 / 7393969305877	
Design / Wood Species	Plank / Oak	
Surface treatment /	Oil / Stained	
Natural/Stained		
Design features	Handscraped, Brushed, Bevelled 4-sided	
Width x Length x Thickness	190 x 1900 x 15 mm	
Weight per package / per	17 kg / 7.73 kg	
m2		
Area per package / per	2.17 m ² / 75.95 m ²	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5G	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-3 times	
Core material	Pine/Spruce	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

PRODUCT	DETAILS
INODOCI	

Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs 2025-09-09

Other products in this collection







MAPLE CAROB




OAK CONCRETE



OAK STRAW







OAK EARTH



OAK CAMINO