



## **OAK UNICO**

The rich toffee stain on this smoked, single-strip floor from the Da Capo Collection gives it its balanced yet rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Decorative butterfly joints add to its crafted complexion. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which emphasises the worn appearance of the floor.

PRODUCT DETAILS		PRODUC
Product type / Construction	Wood Floors / 3-layer parquet	Hardness
Article Number / EAN Code	151XDDEKFPKW195 / 7393969045452	range
Design / Wood Species	Plank / Oak	Warranty
Surface treatment /	Oil / Natural	TECHNIC
Natural/Stained		
Design features	Bevelled 4-sided, Brushed, Smoked,	Moisture
	Handscraped, Wooden plugs	Minimun I
Width x Length x Thickness	190 x 1900 x 15 mm	— kg/m³
Weight per package / per	19 kg / 8.64 kg	Reaction 1
m2		Formaldel
Area per package / per	2.17 m <sup>2</sup> / 75.95 m <sup>2</sup>	Content P
pallet	2.17 111 7 73.33 111	Breaking S
·	Everyopeine	— Thermal C
Grading	Expressive	Biological
Joint	Woodloc® 5G	CARB2
Installation method	Glue-down, Floating	
Floor heating	Yes	Slip resist
Wear leayer material /	Hardwood / 3.5 mm	TSCA
thickness		CARB P2
Resandable	2-4 times	Compliant
Core material	Pine/Spruce	
Backside material	Veneer	

PRODUCT D	<b>ETAILS</b>
-----------	---------------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD











## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occuring wood color variations and create further contrast between light and dark.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Smoked product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | ©Kährs

## Other products in this collection







OAK DECORUM



OAK DOMO



OAK DUSSATO







OAK SPARUTO





OAK INDOSSATI OAK MAGGIORE