



## OAK FARTH

The smoked finish on this single-strip oak floor from the Artisan Collection enhances the natural color variations for a rustic expression. Knots and cracks pepper the boards, adding depth and balancing the toasted sesame seed highlights. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided beveling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

	PRODUCT DETA
Wood Floors / 3-layer parquet	Hardness (Brinell)
151YCDEKFCKW195 / 7393969305860	range
Plank / Oak	Warranty
Oil / Natural	TECHNICAL PRO
	-
Bevelled 4-sided, Brushed, Smoked,	Moisture content
Handscraped	Minimun Mean De
190 x 1900 x 15 mm	
17 kg / 7 83 kg	Reaction To Fire
., ., ., ., ., .,	Formaldehyde Emi
2.47 2.175.05 2	Content PCP
2.17 m² / /5.95 m²	Breaking Strength
	Thermal Conductiv
Dynamic	Biological Durabilit
Woodloc® 5G	CARB2
Floating, Glue-down	
Yes	Slip resistance
Hardwood / 3.5 mm	(MESSICHEL DANS LAUR SYTÉRIEUT)
	A+
2-3 times	_
Pine/Spruce	
Veneer	
	151YCDEKFCKW195 / 7393969305860  Plank / Oak  Oil / Natural  Bevelled 4-sided, Brushed, Smoked, Handscraped  190 x 1900 x 15 mm  17 kg / 7.83 kg  2.17 m² / 75.95 m²  Dynamic  Woodloc® 5G  Floating, Glue-down  Yes  Hardwood / 3.5 mm  2-3 times  Pine/Spruce

PRODUCT	DETAILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



## **DETAILED DESCRIPTION**

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Partly filled knots and cracks will be present in all sizes and numbers. Any flaking in the wood-surface is due to the hand-crafting technique used on the surface to create the design and is permitted without restriction.

Oil: This floor should be oiled immediately after installation.

Colour change: The smoked finish accentuates the natural color variations, creating a stronger contrast between light and dark tones initially. Over time, the color variations will soften, resulting in a more uniform overall appearance. The oiled surface will develop a natural patina.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

www.kahrs.com | ©Kährs

## Other products in this collection







MAPLE CAROB




OAK CONCRETE



OAK STRAW







OAK EARTH



OAK CAMINO