



OAK FOSCHIA

The warm stone hues in this single-strip oak floor from the Domani Collection highlight its rustic expression. Knots and cracks pepper the boards, resulting in a beautifully aged effect reminiscent of reclaimed timber. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

	PRODUCT DETAILS
Wood Floors / 3-layer parquet	Hardness (Brinell) value /
151XCDEKWKKW195 / 7393969045346	range
Plank / Oak	Warranty
Oil / Stained	TECHNICAL PROPERTIE
	— Moisture content
Handscraped, Microbevelled 4-sided	— Minimun Mean Density
190 x 1900 x 15 mm	— kg/m ³
17.1 kg / 7.77 kg	Reaction To Fire
	Formaldehyde Emission
2.17 m ²	— Content PCP
Dynamic	— Breaking Strength N/mm²
Woodloc® 5G	— Thermal Conductivity
Floating, Glue-down	Biological Durability
Yes	— CARB2
Hardwood / 3.5 mm	
	Slip resistance
2-3 times	TSCA UNITARY OF THE PROPERTY O
Spruce	CARB P2
Veneer	Compliant STAN ON BAS
	151XCDEKWKKW195 / 7393969045346 Plank / Oak Oil / Stained Handscraped, Microbevelled 4-sided 190 x 1900 x 15 mm 17.1 kg / 7.77 kg 2.17 m² Dynamic Woodloc® 5G Floating, Glue-down Yes Hardwood / 3.5 mm 2-3 times Spruce

PROD	UCT	DETA	ILS

` ,	,	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Clip resistance	CENITC1E676	NDD

3.7 / 2.2 - 5.9









DETAILED DESCRIPTION

Knots, cracks and uneven fillings is part of the design. These may change in apperance over the years.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

