

Model: SANTORINI BONE 59,6X150(A)

Codes: 100363917

Tone variations: V2

Rectified: Yes



 Sistema DAP®
Declaración Ambiental de
Productos de Construcción

DIMENSIONAL FEATURES UNE-EN ISO 10545-2

Thickness	10.5	+/-5%*
Width	596 mm	
Length	1500 mm	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

*ISO-13006:2018 UNE-EN 14411:2016

FEATURES

 General deshaded design with a degree of color and appearance variation.

 Name given to the finish of those tiles dimensionally improved after the firing process.

MECHANICAL FEATURES UNE-EN ISO 10545-4-6-7-11

Crazing resistance Resists 3 cycles

*ISO-13006:2018 UNE-EN 14411:2016

HYGIENIC FEATURES UNE-EN ISO 10545-13-14:1995

Chemical resistance Class "A" for swimming pools and cleaning products
(resists attack). Minimum Class "B" for acids and bases

B Min.*

Stain resistance Class 5. Easy cleaning with water

3 Min.*

*ISO-13006:2018 UNE-EN 14411:2016

DETERMINATION OF LIGHT REFLECTANCE VALUE (LRV) UNE-EN ISO 10545-18:2022

Determination of light reflectance value (Irv) 53.37

PACKING

Sales units per box	2.681924 M2/BOX
Sales units per pallet	53.638477 M2/PAL
Sales units per unit	0.893975 M2/PIECE

System Certification



RECOMMENDED USE LOCATIONS

Various

Cladding of bonded or mixed facades

Facade cladding with mechanical anchors

System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.