


Model: LINKFLOOR CHEVRON BEIGE  
Codes: 100363688  
Group: G-234  
Format: 30,5X71,84X0,73CM



COMPOSITION



|         | Size | Material   | Type of material |
|---------|------|------------|------------------|
| Layer 1 | 0,55 | Wear layer | Transparent PVC  |
| Layer 2 | 0,01 | Vinyl      | decorative film  |
| Layer 3 | 2    | PVC        | Solid PVC        |
| Layer 4 | 3,95 | EPC        | Expanded PVC     |
| Layer 5 | 0,8  | IXPE       | IXPE motherboard |

FEATURES

- 

Imitates the surface of wood
- 

Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.
- 

5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
- 

Floor capable of dissipating excess electrical charges and distribute them over its entire surface
- 

There are consistent color changes between pieces.
- 

Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- 

25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
- 

Is suitable for installing on water radiant heating
- 

It is a quick and easy installation system. Adjust the slat to be installed lengthwise to the one already placed and tap it lightly with a rubber hammer and block. It is just as easy to uninstall, which allows it to be quickly dismantled.
- 

Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.

LABORATORY TESTS

|                                        |                          |                   |
|----------------------------------------|--------------------------|-------------------|
| Commercial area class                  | 33                       | EN 16511*         |
| Slip resistance (shod feet)            | R10                      | EN 16165 Anexo B* |
| Impact resistance                      | ≥1800 mm                 | EN 13329+A1*      |
| Resistance to staining                 | Grade 5                  | EN 438-2*         |
| Dimensional stability                  | ≤0.15%                   | EN ISO 23999*     |
| Formaldehyde emissions                 | E1                       | EN 717-1*         |
| Slip resistance (wet pendulum) irhd 55 | CL2 (38)                 | EN 16165 Anexo C* |
| Fire resistance                        | Bfl-S1                   |                   |
| Heat resistance                        | 0.074 M2*K/W             | EN 12664*         |
| Thermal conductivity                   | 0.108 W/M*K              | EN 12664*         |
| Residual footprint                     | ≤0.18 mm                 | EN ISO 24343-1*   |
| Acoustic insulation                    | 150 MM CONCRETE-ΔLw=18dB | ISO 10140-3*      |
| Dynamic coefficient of friction (dcof) | 0.52                     | ANSI 137.1*       |
| Private area class                     | 23                       | EN 16511*         |



| PACKING                      |                   |  |
|------------------------------|-------------------|--|
| Sales units per box          | 2.19106 M2/BOX    |  |
| Sales units per pallet       | 78.878177 M2/PAL  |  |
| Sales units per unit         | 0.219106 M2/PIECE |  |
| Sale unit                    | M2                |  |
| Base unit                    | ST                |  |
| Sales units per square meter | 1 M2              |  |
| Net weight                   | 8.813084 KG/M2    |  |
| Gross weight                 | 9.429224 KG/M2    |  |

| SPECIAL PIECES |                                          |       |               |                 |                 |     |            |                |                |
|----------------|------------------------------------------|-------|---------------|-----------------|-----------------|-----|------------|----------------|----------------|
| SAP            | Description                              | Group | Boxes         | Pallet          | Units           | SKU | Basic Unit | Net Weight     | Gross weight   |
| 100366189      | PERF. ADH. LINKFLOOR CHEVRON BEIGE 4X250 | G-155 | 30 PIECES/BOX | 3000 PIECES/PAL | 10 PIECES/M2    | -   | -          | 0.7 KG/PIECES  | 0.72 KG/PIECES |
| 100257147      | PERFIL ADH LINKFLOOR ALUMINIO 3,5X270    | G-121 | 40 PIECES/BOX | 1000 PIECES/PAL | 10.58 PIECES/M2 | -   | -          | 0.37 KG/PIECES | 0.39 KG/PIECES |
| 100366178      | ZOCALO LINKFLOOR PVC CHEVRON BEIGE 8X223 | G-113 | 12 PIECES/BOX | 648 PIECES/PAL  | 5.61 PIECES/M2  | -   | -          | 1.1 KG/PIECES  | 1.25 KG/PIECES |
| 100343146      | ZOCALO PVC PAPEL BLANCO 8X223X1,4        | G-113 | 12 PIECES/BOX | 648 PIECES/PAL  | 5.61 PIECES/M2  | -   | -          | 1.41 KG/PIECES | 1.49 KG/PIECES |

