

Model: LINKFLOOR CHEVRON BROWN**Codes:** 100363687**Group:** G-234**Format:** 30,5X71,84X0,73CM

COMPOSITION



	Size	Material	Type of material
Layer 1	0,55	Wear layer	Transparent PVC
Layer 2	0,01	Vinyl	decorative film
Layer 3	2	PVC	Solid PVC
Layer 4	3,95	EPC	Expanded PVC
Layer 5	0,8	IXPE	IXPE motherboard

FEATURES



Imitates the surface of wood



Water and moisture resistant flooring, suitable for wet areas such as bathrooms and kitchens for residential use, provided the product's installation instructions are followed.



5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Floor capable of dissipating excess electrical charges and distribute them over its entire surface



There are consistent color changes between pieces.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Is suitable for installing on water radiant heating



It is a quick and easy installation system. Adjust the slat to be installed lengthwise to the one already placed and tap it lightly with a rubber hammer and block. It is just as easy to uninstall, which allows it to be quickly dismantled.



Suitable for bathroom and kitchen floors for residential use, provided that the product's installation instructions are always followed.

LABORATORY TESTS

Commercial area class	33	EN 16511*
Slip resistance (shod feet)	R10	EN 16165 Anexo B*
Impact resistance	≥1800 mm	EN 13329+A1*
Resistance to staining	Grade 5	EN 438-2*
Dimensional stability	≤0.15%	EN ISO 23999*
Formaldehyde emissions	E1	EN 717-1*
Slip resistance (wet pendulum) irhd 55	CL2 (38)	EN 16165 Anexo C*
Fire resistance	Bfl-S1	
Heat resistance	0.074 M2*K/W	EN 12664*
Thermal conductivity	0.108 W/M*K	EN 12664*
Residual footprint	≤0.18 mm	EN ISO 24343-1*
Acoustic insulation	150 MM CONCRETE-ΔLw=18dB	ISO 10140-3*
Dynamic coefficient of friction (dcof)	0.52	ANSI 137.1*
Private area class	23	EN 16511*



PACKING

Sales units per box	2.19106 M2/BOX
Sales units per pallet	78.878177 M2/PAL
Sales units per unit	0.219106 M2/PIECE
Sale unit	M2
Base unit	ST
Sales units per square meter	1 M2
Net weight	8.835904 KG/M2
Gross weight	9.452044 KG/M2

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100366220	PERF. ADH. LINKFLOOR CHEVRON BROWN 4X250	G-155	30 PIECES/BOX	3000 PIECES/PAL	10 PIECES/M2	-	-	0.7 KG/PIECES	0.72 KG/PIECES
100257147	PERFIL ADH LINKFLOOR ALUMINIO 3,5X270	G-121	40 PIECES/BOX	1000 PIECES/PAL	10.58 PIECES/M2	-	-	0.37 KG/PIECES	0.39 KG/PIECES
100366179	ZOCALO LINKFLOOR PVC CHEVRON BROWN 8X223	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.1 KG/PIECES	1.25 KG/PIECES
100343146	ZOCALO PVC PAPEL BLANCO 8X223X1,4	G-113	12 PIECES/BOX	648 PIECES/PAL	5.61 PIECES/M2	-	-	1.41 KG/PIECES	1.49 KG/PIECES

