L'ANTIC COLONIAL

Model: KENT DECO JADE GLOSS

Codes: 100363531 Group: G-222

Format: 8X30X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
	100043200 TIXOCEWI E03 23KG	
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

FEATURES



Material with surface with the ability to produce reflections.



Material suitable for use on indoor walls.



No changes in color between pieces.



Material suitable for use on shower walls.



Material that features unevenness on the surface.



Material recommended for installation on walls.

DIMENSIONAL FEATURES				
Length and width deviation	±0.5%	UNE-EN ISO 10545-2*		
Side straightness deviation	±0.3 %	UNE-EN ISO 10545-2*		
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*		
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*		

	PHYSICAL PROPERTIES	
Water absorption	BIII	
Breaking strength	>900 N	>600N*
Coefficient of linear thermal expansion	<6.6 1/(10E6*K)	
Crack resistance	PASS	ISO 10545-11*
Flammability	A1	EN 13501-1*

	PACKING	
Sales units per box	0.672 M2/BOX	
Sales units per pallet	67.2 M2/PAL	
Sales units per unit	0.024 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	10.875 KG/M2	
Gross weight	11.208333 KG/M2	





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

100363531

KENT DECO JADE GLOSS

L'ANTIC COLONIAL

CHEMICAL PROPERTIES				
Stain resistance	Clase 5	ISO 10545-14*		
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*		



