

**Model:** PARMA COTTO**Codes:** 100322864**Group:** G-222**Format:** 30X30X0,85CM

### RECOMMENDATIONS

Recommended adhesive	100201526 ONE-FLEX PREMIUM BLANCO 25KG
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG
Recommended adhesive (wet area)	100201526 ONE-FLEX PREMIUM BLANCO 25KG

### DIMENSIONAL FEATURES

Length and width deviation	±0.5%	UNE-EN ISO 10545-2*
Side straightness deviation	±0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	±0.5%	UNE-EN ISO 10545-2*
Surface flatness deviation	±0.5 %	UNE-EN ISO 10545-2*

### FEATURES

-  Gloss-free
-  Material suitable for use on shower walls.
-  Material suitable for use on outdoor walls.
-  Material suitable for use on indoor walls.
-  Material suitable for use on indoor floors.
-  There are consistent color changes between pieces.
-  Material recommended for installation on the floor.

### PHYSICAL PROPERTIES

Water absorption	Bla	ISO 10545-3*
Breaking strength	>2100 N	>1300N*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Flexural strength	>51 MPA	ISO 10545-4*
Slip resistance (wet pendulum) irhd 55	CL 1 (24)	EN 16165 Anexo C*
Slip resistance (shod feet)	R-10	EN 16165 Anexo B*
Slip resistance (pendulum-dry)	90	
Dynamic coefficient of friction (dcof)	0.44	
Abrasion resistance	PEI 3	



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

## CHEMICAL PROPERTIES

Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*

## PACKING

Sales units per box	0.99 M2/BOX
Sales units per pallet	47.52 M2/PAL
Sales units per unit	0.09 M2/PIECE
Sale unit	M2
Base unit	ST
Net weight	19.711111 KG/M2
Gross weight	20.177778 KG/M2



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.