

Model: GEO GREY  
Codes: 100350747  
Group: G-213  
Format: 12,35X44,3X0,85CM



| RECOMMENDATIONS                 |                                         |  |
|---------------------------------|-----------------------------------------|--|
| Recommended adhesive            | 100043280 TIXOCEM PLUS 25KG             |  |
| Recommended joint               | 100236449 COLORSTUK RAPID CEMENTO N 5KG |  |
| Recommended joint (wet area)    | 100236449 COLORSTUK RAPID CEMENTO N 5KG |  |
| Recommended adhesive (wet area) | 100043280 TIXOCEM PLUS 25KG             |  |

| DIMENSIONAL FEATURES        |        |                     |
|-----------------------------|--------|---------------------|
| Length and width deviation  | ±0.5%  | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.3 % | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | ±0.5%  | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | ±0.5 % | UNE-EN ISO 10545-2* |

| FEATURES                                                                                                                            |                                                                                                                                |
|-------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
|  Gloss-free                                      |  Material suitable for use on shower walls. |
|  Material suitable for use on indoor walls.      |  No changes in color between pieces.        |
|  Material recommended for installation on walls. |                                                                                                                                |

| PHYSICAL PROPERTIES |       |               |
|---------------------|-------|---------------|
| Water absorption    | BIII  | ISO 10545-2*  |
| Breaking strength   | 875 N | >600N*        |
| Crack resistance    | PASS  | ISO 10545-11* |
| Flammability        | A1    | EN 13501-1*   |

| CHEMICAL PROPERTIES     |            |               |
|-------------------------|------------|---------------|
| Stain resistance        | Clase 5    | ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA | ISO 10545-13* |



| PACKING                |                  |  |
|------------------------|------------------|--|
| Sales units per box    | 1.313043 M2/BOX  |  |
| Sales units per pallet | 89.286957 M2/PAL |  |
| Sales units per unit   | 0.05471 M2/PIECE |  |
| Sale unit              | M2               |  |
| Base unit              | ST               |  |
| Net weight             | 14.129007 KG/M2  |  |
| Gross weight           | 14.384901 KG/M2  |  |

