

Model: HERITAGE VALENCIA

Codes: 100336807

Group: G-226

Format: 20X20X0,85CM



| RECOMMENDATIONS                 |                                      |  |
|---------------------------------|--------------------------------------|--|
| Recommended adhesive            | 100201543 ONE-FLEX PREMIUM GRIS 25KG |  |
| Recommended joint               | 100236834 COLORSTUK RAPID GRIS N 5KG |  |
| Recommended joint (wet area)    | 100236834 COLORSTUK RAPID GRIS N 5KG |  |
| Recommended adhesive (wet area) | 100201543 ONE-FLEX PREMIUM GRIS 25KG |  |

| DIMENSIONAL FEATURES        |        |                     |
|-----------------------------|--------|---------------------|
| Length and width deviation  | ±0.5%  | UNE-EN ISO 10545-2* |
| Side straightness deviation | ±0.5 % | UNE-EN ISO 10545-2* |
| Orthogonality deviation     | ±0.5%  | UNE-EN ISO 10545-2* |
| Surface flatness deviation  | ±0.5 % | UNE-EN ISO 10545-2* |

| FEATURES                                                                                                                                |                                                                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
|  Gloss-free                                          |  Material suitable for use on shower walls.     |
|  Material suitable for use on outdoor walls.         |  Material suitable for use on indoor walls.     |
|  Material suitable for use on indoor floors.         |  There are slight color changes between pieces. |
|  Material recommended for installation on the floor. |                                                                                                                                    |

| PHYSICAL PROPERTIES                    |           |                   |
|----------------------------------------|-----------|-------------------|
| Water absorption                       | Bla       | ISO 10545-3*      |
| Breaking strength                      | >2100 N   | >1300N*           |
| Resistance to thermal shock            | PASS      | ISO 10545-9*      |
| Crack resistance                       | PASS      | ISO 10545-11*     |
| Flammability                           | A1f I/A1  | EN 13501-1*       |
| Flexural strength                      | >51 MPA   | ISO 10545-4*      |
| Slip resistance (wet pendulum) irhd 55 | CL 1 (28) | EN 16165 Anexo C* |
| Slip resistance (shod feet)            | R9        | EN 16165 Anexo B* |
| Slip resistance (pendulum-dry)         | 80        |                   |
| Dynamic coefficient of friction (dcof) | 0.72      |                   |
| Abrasion resistance                    | PEI 3     |                   |



| CHEMICAL PROPERTIES     |            |               |
|-------------------------|------------|---------------|
| Stain resistance        | CL 5       | ISO 10545-14* |
| Resistance to chemicals | GA/GLA/GHA | ISO 10545-13* |

| PACKING                |               |  |
|------------------------|---------------|--|
| Sales units per box    | 0.88 M2/BOX   |  |
| Sales units per pallet | 52.8 M2/PAL   |  |
| Sales units per unit   | 0.04 M2/PIECE |  |
| Sale unit              | M2            |  |
| Base unit              | ST            |  |
| Net weight             | 20.225 KG/M2  |  |
| Gross weight           | 20.625 KG/M2  |  |

