









Model: CUZCO BONE  
Codes: 100363675  
Group: G-227  
Format: 20X23,2X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100201543 ONE-FLEX PREMIUM GRIS 25KG	
Recommended joint	100236834 COLORSTUK RAPID GRIS N 5KG	
Recommended joint (wet area)	100236834 COLORSTUK RAPID GRIS N 5KG	
Recommended adhesive (wet area)	100201543 ONE-FLEX PREMIUM GRIS 25KG	

FEATURES	
 Gloss-free	 Material suitable for use on shower walls.
 Material suitable for use on outdoor walls.	 Material suitable for use on indoor walls.
 Material suitable for use on indoor floors.	 There are considerable color changes between pieces.
 Material recommended for installation on the floor.	 Models with this symbol need to be grouted across the whole surface.

PHYSICAL PROPERTIES		
Water absorption	Bla	ISO 10545-3*
Breaking strength	3738.9 N	>1300N*
Coefficient of linear thermal expansion	<6.6 1/(10E6*K)	
Resistance to thermal shock	RESISTE	
Crack resistance	RESISTE 3 CICLOS	
Slip resistance (wet pendulum) irhd 55	CL1 (25)	
Slip resistance (pendulum-dry)	>40	
Dynamic coefficient of friction (dcof)	0.66	
Abrasion resistance	PEI 4 / 1500v	

CHEMICAL PROPERTIES		
Stain resistance	CLASE 5	
Resistance to chemicals	MÍNIMO CLASE B	



PACKING		
Sales units per box	0.9022 M2/BOX	
Sales units per pallet	54.132 M2/PAL	
Sales units per unit	0.0347 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	17.809798 KG/M2	
Gross weight	18.184438 KG/M2	

