


**Model:** BALI KUTA MATT**Codes:** 100340700**Group:** G-226**Format:** 14,7X14,7X0,85CM

### RECOMMENDATIONS

Recommended adhesive 100201526 ONE-FLEX PREMIUM BLANCO 25KG

Recommended joint 100236834 COLORSTUK RAPID GRIS N 5KG

Recommended joint (wet area) 100182208 EPOTECH AQUA GRIS 1,5KG

Recommended adhesive (wet area) 100142757 SUPER-FLEX S2 15KG

### DIMENSIONAL FEATURES

Length and width deviation ±0.5% UNE-EN ISO 10545-2\*

Side straightness deviation ±0.5% UNE-EN ISO 10545-2\*

Orthogonality deviation ±0.5% UNE-EN ISO 10545-2\*

Surface flatness deviation ±0.5% UNE-EN ISO 10545-2\*

### FEATURES



Gloss-free



Material suitable for use on shower walls.



Material suitable for use on indoor walls.



Material suitable for use on shower floors.



There are considerable color changes between pieces.



Material suitable for use on pool surroundings.



Material suitable for use on outdoor walls.



Material suitable for use on permanently wet areas.



Material suitable for use on outdoor floors.



Material recommended for installation on the floor.

### ADDITIONAL NOTES

For swimming pools, follow the installation and maintenance instructions, as well as the instructions for the recommended SUPER FLEX S2 adhesive and EPOTECH AQUA grout. In these applications, it is necessary to waterproof the substrate, install a minimum joint of 5 mm, and install expansion joints.



## PHYSICAL PROPERTIES

Water absorption	Bla	ISO 10545-3*
Breaking strength	>1800 N	>1300N*
Resistance to thermal shock	PASS	ISO 10545-9*
Crack resistance	PASS	ISO 10545-11*
Flammability	A1f I/A1	EN 13501-1*
Slip resistance (wet pendulum) irhd 55	CL 3 (49)	EN 16165 Anexo C*
Slip resistance (shod feet)	R10	EN 16165 Anexo B*
Slip resistance (pendulum-dry)	98	
Dynamic coefficient of friction (dcof)	0.78 (T7C1K)	
Abrasion resistance	PEI 3	ISO 10545-7*
Slip resistance (wet pendulum) (aus) irhd 55	54 (T7C1K)	
Slip resistance (wet pendulum) (aus) irhd 96	54 (T7C1K)	

## CHEMICAL PROPERTIES

Stain resistance	CL 5	ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	ISO 10545-13*

## PACKING

Sales units per box	0.302526 M2/BOX
Sales units per pallet	54.454665 M2/PAL
Sales units per unit	0.021609 M2/PIECE
Sale unit	M2
Base unit	ST
Net weight	19.806568 KG/M2
Gross weight	20.176784 KG/M2

