L'ANTIC COLONIAL

Model: CUZCO DUAL TERRA

Codes: 100363499 Group: G-227

Format: 20X23,2X0,85CM



RECOMMENDATIONS		
Recommended adhesive	100201543 ONE-FLEX PREMIUM GRIS 25KG	
Recommended joint	100353483 COLORSTUK RAPID ASH N 5KG	
Recommended joint (wet area)	100353483 COLORSTUK RAPID ASH N 5KG	
Recommended adhesive (wet area)	100201543 ONE-FLEX PREMIUM GRIS 25KG	

FEATURES



Gloss-free



Material suitable for use on outdoor walls.




Material suitable for use on indoor floors.



Material recommended for installation on the floor.

_	
	7
	/T/





Material suitable for use on indoor walls.



There are considerable color changes between pieces.

	PHYSICAL PROPERTIES	
Water absorption	Bla	ISO 10545-3*
Breaking strength	3738.9 N	>1300N*
Resistance to thermal shock	RESISTE	
Crack resistance	RESISTE 3 CICLOS	
Slip resistance (wet pendulum) irhd 55	CL1 (20)	
Slip resistance (pendulum-dry)	>40	
Dynamic coefficient of friction (dcof)	0.64	
Abrasion resistance	DEL / / 1500v	

	PACKING
Sales units per box	0.9022 M2/BOX
Sales units per pallet	54.132 M2/PAL
Sales units per unit	0.0347 M2/PIECE
Sale unit	M2
Base unit	ST
Net weight	17.809798 KG/M2
Gross weight	18.184438 KG/M2





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.