

Model: CUZCO LIGHT  
Codes: 100363672  
Group: G-227  
Format: 20X23,2X0,85CM



| RECOMMENDATIONS                 |                                      |  |
|---------------------------------|--------------------------------------|--|
| Recommended adhesive            | 100201543 ONE-FLEX PREMIUM GRIS 25KG |  |
| Recommended joint               | 100236834 COLORSTUK RAPID GRIS N 5KG |  |
| Recommended joint (wet area)    | 100236834 COLORSTUK RAPID GRIS N 5KG |  |
| Recommended adhesive (wet area) | 100201543 ONE-FLEX PREMIUM GRIS 25KG |  |

| FEATURES                                                                                                                                |                                                                                                                                          |
|-----------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
|  Gloss-free                                          |  Material suitable for use on shower walls.           |
|  Material suitable for use on outdoor walls.         |  Material suitable for use on indoor walls.           |
|  Material suitable for use on indoor floors.         |  There are considerable color changes between pieces. |
|  Material recommended for installation on the floor. |                                                                                                                                          |

| PHYSICAL PROPERTIES                    |                  |              |
|----------------------------------------|------------------|--------------|
| Water absorption                       | Bla              | ISO 10545-3* |
| Breaking strength                      | 3738.9 N         | >1300N*      |
| Resistance to thermal shock            | RESISTE          |              |
| Crack resistance                       | RESISTE 3 CICLOS |              |
| Slip resistance (wet pendulum) irhd 55 | CL1 (31)         |              |
| Slip resistance (pendulum-dry)         | >40              |              |
| Dynamic coefficient of friction (dcof) | 0.67             |              |
| Abrasion resistance                    | PEI 4 / 1500v    |              |

| PACKING                |                 |  |
|------------------------|-----------------|--|
| Sales units per box    | 0.9022 M2/BOX   |  |
| Sales units per pallet | 54.132 M2/PAL   |  |
| Sales units per unit   | 0.0347 M2/PIECE |  |
| Sale unit              | M2              |  |
| Base unit              | ST              |  |
| Net weight             | 17.809798 KG/M2 |  |
| Gross weight           | 18.184438 KG/M2 |  |

