

Model: CUZCO DUAL CONCRETE

Codes: 100363671

Group: G-227

Format: 20X23,2X0,85CM



RECOMMENDATIONS

Recommended adhesive	100201543 ONE-FLEX PREMIUM GRIS 25KG
Recommended joint	100236481 COLORSTUK RAPID ANTRACITA N 5KG
Recommended joint (wet area)	100236481 COLORSTUK RAPID ANTRACITA N 5KG
Recommended adhesive (wet area)	100201543 ONE-FLEX PREMIUM GRIS 25KG

FEATURES

	Gloss-free		Material suitable for use on shower walls.
	Material suitable for use on outdoor walls.		Material suitable for use on indoor walls.
	Material suitable for use on indoor floors.		There are considerable color changes between pieces.
	Material recommended for installation on the floor.		

PHYSICAL PROPERTIES

Water absorption	Bla	ISO 10545-3*
Breaking strength	3738.9 N	>1300N*
Resistance to thermal shock	RESISTE	
Crack resistance	RESISTE 3 CICLOS	
Slip resistance (wet pendulum) irhd 55	CL1 (21)	
Slip resistance (pendulum-dry)	>40	
Dynamic coefficient of friction (dcof)	0.62	
Abrasion resistance	PEI 4 / 1500v	

PACKING

Sales units per box	0.9022 M2/BOX
Sales units per pallet	54.132 M2/PAL
Sales units per unit	0.0347 M2/PIECE
Sale unit	M2
Base unit	ST
Net weight	17.809798 KG/M2
Gross weight	18.184438 KG/M2

