

**Model:** CADORE WENGE NAT. 120X270(6)(A)

**Codes:** 100355454

**Absorption:** Bla - Porcelanico ( $E \leq 0.1\%$ )

**Finish:** Standard

**Tone variations:** V3

**Rectified:** Yes



## DIMENSIONAL FEATURES

UNE-EN ISO 10545-2

Length	2700 mm	
Thickness	6 mm	
Width	1200 mm	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

\*ISO-13006:2015 UNE-EN 14411:2017

## FEATURES

Natural-looking, non-glossy surface finish.

ECLIPSE

Name given to the finish of those tiles dimensionally improved after the firing process.

Installation on floor

## MECHANICAL FEATURES

UNE-EN ISO 10545-4-6-7-11

Breaking strength	>1100 N
Modulus of rupture	> 45 N/mm <sup>2</sup>
Abrasion resistance	<140 mm <sup>3</sup>
Qb-wallpec (e)	NO APLICA
Qb-wallpec (c)	NO APLICA

\*ISO-13006:2015 UNE-EN 14411:2017

## HYGIENIC FEATURES

UNE-EN ISO 10545-13-14

Chemical resistance	MIN B
Stain resistance	5
Flammability	A1

\*ISO-13006:2015 UNE-EN 14411:2017

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.

## ANTI-SLIP VALUE

CEN/TS 41901/02, DIN-51130 y ASTM A137.1

Slip resistance (wet pendulum) irhd 55 CL1 PTV 22 (tono H102)\*

Slip resistance (shod feet) R-9 8º (tono H102)\*

Slip resistance (pendulum-dry) &gt;40

\*ISO-13006:2015 UNE-EN 14411:2017

## ADDITIONAL NOTES

\*COMPOSITION WITH CONTINUITY, MAXIMUM DEVIATION IN GRAPHIC CONTINUITY BETWEEN PIECES 1.5 CM

## DETERMINATION OF LIGHT REFLECTANCE VALUE (LRV)

UNE-EN ISO 10545-18:2022

Determination of light reflectance value (lrv) 13

## PACKING

Sales units per box 3.240441 M2/BOX

Sales units per pallet 71.289695 M2/PAL

Sales units per unit 3.240441 M2/PIECE

## SCOPE OF USE

Technical code-1 4 - Light Transit with Direct Access to the Outdoors

Technical code-2 0 - No additional requirements

## System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.