Model: LINES BOLL ASTON CLASSICO
Codes: 100310050
Group: G-118
Format: 30,35X25,53CM



RECOMMENDATIONS

Recommended adhesive	100031188 SUPER-ONE N BLANCO 25KG	
Recommended joint	100204245 COLORSTUK ESPECIAL ASH 2KG	
Recommended joint (wet area)	100204245 COLORSTUK ESPECIAL ASH 2KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100031188 SUPER-ONE N BLANCO 25KG	

TECHNICAL INFORMATION

Slip resistance (wet pendulum) irhd 55	CL 1 (28)	EN 16165 Anexo C*
Slip resistance (pendulum-dry)	80	
Flammability	Clase A1f l/Clase A1	UNE-EN 13501-1:2007+A1:2010*
Use	FLOOR TILES	
Dynamic coefficient of friction (dcof)	0.63	ANSI 137.1*
Composition	MARBLE	

FEATURES

- Product manufactured on a mesh that makes installation easier.
- Gloss-free
- Material suitable for use on shower floors.
- Material only suitable for low-traffic floors (private setting.)
- Material suitable for use on indoor floors.
- Material suitable for use on shower walls.
- Material suitable for use on indoor walls.

PACKING

Sales units per square meter	12.905967 PIECES/M2	
Sales units per box	10 PIECES/BOX	
Sales units per unit	1 PIECES	
Sale unit	ST	
Base unit	ST	
Net weight	2.14 KG/PIECES	
Gross weight	2.215 KG/PIECES	

It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive agents, such as acids or solvents, or metallic or sharp elements for cleaning. In public places mosaics must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.