Model: CUZCO WHITE
Codes: 100363673
Group: G-227
Format: 20X23,2X0,85CM



RECOMMENDATIONS

Recommended adhesive	100043280 TIXOCEM PLUS 25KG	
Recommended joint	100236834 COLORSTUK RAPID GRIS N 5KG	
Recommended joint (wet area)	100236834 COLORSTUK RAPID GRIS N 5KG	
Recommended adhesive (wet area)	100043280 TIXOCEM PLUS 25KG	

DIMENSIONAL FEATURES

Length and width deviation	0.5 %	UNE-EN ISO 10545-2*
Side straightness deviation	0.5 %	UNE-EN ISO 10545-2*
Orthogonality deviation	0.5 %	UNE-EN ISO 10545-2*
Surface flatness deviation	0.5 %	UNE-EN ISO 10545-2*

FEATURES

- Gloss-free
- Material suitable for use on shower walls.
- Material suitable for use on outdoor walls.
- Material suitable for use on indoor walls.
- Material suitable for use on indoor floors.
- Material recommended for installation on the floor.

PHYSICAL PROPERTIES

Water absorption	BIa	UNE-EN ISO 10545-3*
Breaking strength	4430.6 N	>1300 N*
Resistance to thermal shock	RESISTE	UNE-EN ISO 10545-9*
Crack resistance	RESISTE 3 CICLOS	UNE-EN ISO 10545-11*
Flammability	A1; A1fl	EN 13501-1*
Slip resistance (wet pendulum) irhd 55	25 (CL1)	UNE-EN 16165 Anexo C*
Dynamic coefficient of friction (dcof)	0.65	ANSI A326.3*
Abrasion resistance	PEI 4	UNE-EN ISO 10545-7*

CHEMICAL PROPERTIES

Stain resistance	Clase 5	UNE-EN ISO 10545-14*
Resistance to chemicals	GA/GLA/GHA	UNE-EN ISO 10545-13*

It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.

PACKING

Sales units per box	0.9022 M2/BOX	
Sales units per pallet	54.132 M2/PAL	
Sales units per unit	0.0347 M2/PIECE	
Sale unit	M2	
Base unit	ST	
Net weight	17.809798 KG/M2	
Gross weight	18.184438 KG/M2	

It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use cleaning agents containing hydrofluoric acid. In public places the tiles must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.